







SYMBOL	CHARACTERISTIC	SERIES 1	SERIES 2	SERIES 3	SERIES 4	PILOT RATIO	
<p>3-port non-vented</p> 		T-11A	T-2A	T-17A	T-19A		
		15 gpm (60 L/min)	30 gpm (120 L/min)	60 gpm (240 L/min)	120 gpm (480 L/min)		
	Standard	CBCL	CBEL	CBGL	CBIL		2.3:1
		CBCY	CBEY	CBGY	CBIY		2:1
		CBCB	CBEB	CBGB	CBIB		1.5:1
		CBCA	CBEA	CBGA	CBIA		3:1
		CBCG	CBEG	CBGG	CBIG		4.5:1
		CBCH	CBEH	CBGH	CBIH		10:1
			10 gpm (40 L/min)	20 gpm (80 L/min)	40 gpm (160 L/min)		
	Semi-restrictive	CBBB	CBDB	CBFB			1.5:1
		CBBL	CBDL	CBFL			2.3:1
		CBBC	CBDC	CBFC			3:1
		CBBD	CBDD	CBFD			4.5:1
			5 gpm (20 L/min)	7.5 gpm (30 L/min)	15 gpm (60 L/min)	20 gpm (80 L/min)	
	Restrictive	CBBY					2:1
		CBBA	CBDA	CBFA	CBHA		3:1
			2.5 gpm (10 L/min)				
	Ultra-restrictive	CBAB					1.5:1
		CBAA					3:1
		CBAG					4.5:1
CBAH						10:1	
<p>3-port non-vented, fixed setting</p> 		15 gpm (60 L/min)	30 gpm (120 L/min)	20 gpm (80 L/min)			
	Standard	CBCLX					2.3:1
		CBCAX	CBEAX				3:1
		CBCGX					4.5:1
		CBCHX					10:1
			10 gpm (40 L/min)	20 gpm (80 L/min)			
	Semi-restrictive	CBBLX					2.3:1
		CBBCX	CBDCX				3:1
		CBBDX	CBDDX				4.5:1
		CBBBX	CBDBX				1.5:1

SYMBOL	CHARACTERISTIC	SERIES 1	SERIES 2	SERIES 3	SERIES 4	PILOT RATIO	
3-port non-vented, fixed setting (continued)		T-11A	T-2A	T-17A	T-19A		
		5 gpm (20 L/min)	7.5 gpm (30 L/min)				
	Restrictive	CBBAX	CBDAX			3:1	
		CBBGX	CBDGX			4.5:1	
		CBBHX	CBDHX			10:1	
3-port vented 		7.5 gpm (30 L/min)					
	Atmospherically vented	CABK				1:1	
		CABG				4.5:1	
		CABN				7:1	
			15 gpm (60 L/min)	30 gpm (120 L/min)	60 gpm (240 L/min)	120 gpm (480 L/min)	
	Standard	CACK	CAEK	CAGK	CAIK	1:1	
		CACL	CAEL	CAGL	CAIL	2:1	
		CACA	CAEA	CAGA	CAIA	3:1	
		CACG	CAEG	CAGG	CAIG	5:1	
		CACH				10:1	
4-port vented 		T-21A	T-22A	T-23A	T-24A		
		15 gpm (60 L/min)	30 gpm (120 L/min)	60 gpm (240 L/min)	120 gpm (480 L/min)		
	Standard	CWCK	CWEK	CWGK	CWIK	1:1	
		CWCL	CWEL	CWGL	CWIL	2:1	
		CWCA	CWEA	CWGA	CWIA	3:1	
CWCG		CWEG	CWGG	CWIG	5:1		
Load-reactive 		T-2A	T-17A	T-19A			
		15 gpm (60 L/min)	30 gpm (120 L/min)	60 gpm (240 L/min)	120 gpm (480 L/min)		
	Load reactive			MBGB	MBIB	1.5:1	
		MBDA	MBEA	MBGA	MBIA	3:1	
		MBEG	MBGG	MBIG	4.5:1		
Load-reactive, vented 		T-22A	T-23A	T-24A			
			30 gpm (120 L/min)	60 gpm (240 L/min)	120 gpm (480 L/min)		
	Load reactive, vented		MWEB			1.5:1	
			MWEA			3:1	
			MWEG	MWGG	MWIG	4.5:1	